



LT 10060 L



MASE GENERATORS S.p.A. Via Tortona, 345 47522 Cesena (FC) Italy Tel.+39-0547-354311 Fax.+39-0547-317555 Email : mase@masegenerators.com www.masegenerators.com



SUPER SILENCED SINGLE-PHASE POWER GENERATOR / OUTPUT POWER 10 kW SINGLE-PHASE / DIESEL ENGINE 1800 RPM

Gen Set Features	 + Control panel with voltmeter and hour meter; with auto engine protection shutdown system in case of: + low oil pressure + high engine temperature 	 + 12V built-in battery with electric start + fuel level gauge + emergency stop push-button + 1x16A 220V single-phase socket protected by circuit breaker + 3 stabilizers + 7 mt lighting tower with 4x1500W halogen lamps + 2 wheels site tow undercarriage
Options (available as factory options)	 + floodlight with metal halide lamps + floodlight with LED lamps + hydraulic lifting 	 + 2 wheels road tow + low temperature kit + dusk sesor + homologation to directive 2000/14/EC
Accessories on Request	+ not available	
Noise Level	+ Lwa 97 (72 dB a 7 m)	
AC Generator 50 Hz	 type: synchronous single-phase power (stand by): 10 kW - 220 V single-phase power (prime): 9 kW - 220 V power Factor: cosΦ0.8 	
Diesel Engine 1500 rpm	 + type: Lombardini LDW 1003 - 3 cyl. 12 HP - 1028 cm³ + fuel: diesel + cooling system: water + starting system: electric + fuel tank capacity: 100 L + fuel consumption @ 75%: 2,4 L/h 	
Other Features	 + insulation Class: H + ambient temperature: 40 °C (*) + altitude: 1000 mt (*) + mechanical Protection: IP 23 + dimensions (L x W x H): 2935 x 1522 x 2395 mm + dimensions of the machine in operation (L x W x H): 2935 x 2612 x 8000 mm + dry weight: 655 kg 	

(*) - For altitude and temperature values higher than those listed above, please consult the manufacturer to verify the available power.